

Pin Configuration for MSD600CIII

Page 1/2

DK-Audio A/S
 Marielundvej 37 D
 2730 Herlev, Denmark
info@dk-audio.com
www.dk-audio.com/

Analogue & AES/EBU Input/Output			
<i>25-Pole DSUB</i>			
Input			
ANA 1	Hot	Pin 14	
	Cold	Pin 1	
	GND	Pin 2	
ANA 2	Hot	Pin 15	
	Cold	Pin 3	
	GND	Pin 16	
AES/EBU 1	Hot	Pin 9	
	Cold	Pin 21	
	GND	Pin 22	
AES/EBU 2	Hot	Pin 10	
	Cold	Pin 23	
	GND	Pin 22	
Output			
ANA 1	Hot	Pin 17	
	Cold	Pin 4	
	GND	Pin 5	
ANA 2	Hot	Pin 18	
	Cold	Pin 6	
	GND	Pin 19	
AES/EBU 1	Hot	Pin 24	
	Cold	Pin 11	
	GND	Pin 12	
AES/EBU 2	Hot	Pin 25	
	Cold	Pin 13	
	GND	Pin 12	
Power, RS232 & I2C			
<i>9-Pole DSUB</i>			
+Vcc	12-15V	Pin 4	
Power ground		Pin 5	
I2C	IRQ	Pin 8	
	SDA	Pin 7	
	SCL	Pin 6	
RS232	TX	Pin 2	
	RX	Pin 3	
GND		Pin 1	



Pin Configuration for MSD600CIII

Page 2/2

DK-Audio A/S
Marielundvej 37 D
2730 Herlev, Denmark
info@dk-audio.com
www.dk-audio.com/

VGA			
<i>15-Pole DSUB</i>			
<i>GND</i>		<i>Pin 5,6,7,8,10</i>	
<i>H-sync</i>		<i>Pin 13</i>	
<i>V-sync</i>		<i>Pin 14</i>	
<i>Red</i>		<i>Pin 1</i>	
<i>Green</i>		<i>Pin 2</i>	
<i>Blue</i>		<i>Pin 3</i>	